

## Description

Super-Rib is our strongest panel which allows for longer spans and a reduction in the number of supports. As a wall panel, Super-Rib side laps in the low cell. As a roof panel, Super-Rib is inverted so that the side lap occurs in the high cell.

All Exposed Fastener wall panels may be installed in a variety of rainscreen applications to form a complete wall system. Systems may vary from an uninsulated screenwall to MetalWrap® Series, an insulated composite backup panel system with Advanced Thermal and Moisture Protection (ATMP®). Refer to CENTRIA Technical bulletin TB-05-10 for all rainscreen applications.

## Notes

- A. For information on special applications, contact your local CENTRIA Representative.
- B. Minimum of roof slope = 1" in 12" [25mm in 305mm].
- C. Panel length tolerance is + or - 1/4" [6mm].
- D. For protective coatings - see CENTRIA Color Chart or visit [www.CENTRIA.com](http://www.CENTRIA.com).
- E. Oil canning within mill tolerances will not be cause for rejection.
- F. Panels must be ordered as "roofing" or "siding" to ensure painting of proper surfaces.
- G. Super-Rib must be inverted for roofing.

## General Design Options

	<b>GALVANIZED<sup>1</sup> (G90)</b>	<b>STAINLESS STEEL<sup>1</sup> (304)</b>	<b>ALUMINUM<sup>1</sup> (3003-H14)</b>
<b>PANEL THICKNESS</b>	4" [102mm]	N/A	4" [102mm]
<b>PANEL COVERAGE</b>	24" [610mm]	N/A	24" [610mm]
<b>SIDE LAP</b>	Overlapping	N/A	Overlapping
<b>END LAPS</b>	Overlapping, Flash	N/A	Overlapping, Flash
<b>GAGES (STANDARD)</b>	20 [.91mm], 22 [.76mm]	N/A	.040 [1.02mm], .050 [1.27mm]
<b>GAGES (OPTIONAL)</b>	18 [1.19mm]	N/A	N/A
<b>STANDARD LENGTH</b>	5 [1.524m] - 40 ft. [12.192m]	N/A	5 [1.524m] - 20 ft. [6.096m]
<b>OPTIONAL LENGTH</b>	1 [.305m] - 5 ft. [1.524m], 40 [12.192m] - 48 ft. [14.630m]	N/A	1 [.305m] - 5 ft. [1.524m]
<b>TEXTURE (STANDARD)</b>	Smooth	N/A	Smooth
<b>TEXTURE (OPTIONAL)</b>	Embossed <sup>2</sup>	N/A	Embossed <sup>2</sup>
<b>FINISHES</b>	See CENTRIA Color Chart	N/A	See CENTRIA Color Chart

- 1. Alternate base material, panel lengths and gages may also be available. Contact CENTRIA.
- 2. Embossing is non-directional.

